

**PRESS® N/L 10****Hose Construction**

- Tube:** Black, smooth SBR nitrosamine free rubber compound
- Reinforcement:** Synthetic textile yarns
- Cover:** Black (N), smooth (/L), abrasion, ageing and weather-resistant SBR/EPDM nitrosamine free rubber compound

**Applications**

Suitable for discharge of water and non-aggressive liquids in many industrial and agricultural applications.

**Temperature Range**

-30 °C (-22 °F) to + 80 °C (+176 °F)

**Tolerances**

According to UNI EN ISO 1307/97

**On inside diameter:**

≤ I.D. 5 mm:	± 0,60 mm
I.D. 8 - 20 mm:	± 0,80 mm
I.D. 22 - 25 mm:	± 1,20 mm
> I.D. 25 mm:	± 1,60 mm
<b>Length tolerance:</b>	± 1 %

IHXXXXXXXX/XX Part Number/ Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Burst Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psi	bar	MPa	psi	bar		
IH30102102/100	5	10,5	1,0	150,0	10	3,0	450,0	30	0,10	30
IH30101001/100	8	15	1,0	150,0	10	3,0	450,0	30	0,19	50
IH30101002/100	10	15	1,0	150,0	10	3,0	450,0	30	0,15	60
IH30101003/100	10	17	1,0	150,0	10	3,0	450,0	30	0,22	60
IH30101004/100	12	17	1,0	150,0	10	3,0	450,0	30	0,17	70
IH30101005/100	13	19	1,0	150,0	10	3,0	450,0	30	0,23	80
IH30101006/100	15	21	1,0	150,0	10	3,0	450,0	30	0,25	90
IH30101007/100	16	23	1,0	150,0	10	3,0	450,0	30	0,32	100
IH30101008/80	19	26	1,0	150,0	10	3,0	450,0	30	0,37	110
IH30101009/80	20	30	1,0	150,0	10	3,0	450,0	30	0,59	120
IH30101010/80	22	30	1,0	150,0	10	3,0	450,0	30	0,49	130
IH30101011/50	25	33	1,0	150,0	10	3,0	450,0	30	0,55	150
IH30101012/50	25	35	1,0	150,0	10	3,0	450,0	30	0,70	150
IH30101013/40	30	42	1,0	150,0	10	3,0	450,0	30	1,00	180
IH30101014/40	32	44	1,0	150,0	10	3,0	450,0	30	1,07	190

Zapraszamy do dystrybutora PARKER ITR:

HOSEMANN POLSKA

[www.hosemann.pl](http://www.hosemann.pl)

biuro@hosemann.pl

RUBBER HOSE PRESS 10 bar MADE IN ITALY Parker ITR