



AUTOGAS ECE 67/110 CLASS 2

According to ECE 67 and 110 Class 2

Low pressure hoses, designed according to regulation ECE 67, 01, Annex 8, Class 2 and ECE 110, 02, Annex 4b, Class 2.

Suitable for low pressure delivery of LPG and methane CNG alternative fuel kits.

Hose Construction

Tube: Black, smooth, insulating (R > 1 MΩ/m), LPG and methane permeation resistant NBR rubber compound

Reinforcement: Synthetic textile yarns

Cover: Black, smooth, insulating (R > 1 MΩ/m), CSM rubber compound resistant to ageing, heat, abrasion, ozone and weathering








- Insulating cover and tube compounds
- Exceeds DIN 4815 Teil 4
- Available pre-formed on request
- Very low permeation values closed to zero
- Burst Pressure Value 4:1

Tolerances

According to UNI EN ISO 1307
Refer to Technical Handbook on page TH34

Temperature Range

-25 °C (-13 °F) to +120 °C (+ 248 °F)

Part Number	 I.D. (mm)	 O.D. (mm)	 Working Pressure			 Weight kg/m	 min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH30510060/50	4	10	0.45	65.0	4.5	0.09	35	Y
IH30510027/50	5	10.5	0.45	65.0	4.5	0.09	40	Y
IH30510061/50	6.3	13	0.45	65.0	4.5	0.14	50	Y
IH30510064/50	10	17	0.45	65.0	4.5	0.20	80	Y
IH30510065/50	12	19	0.45	65.0	4.5	0.23	100	Y
IH30510066/50	14	22	0.45	65.0	4.5	0.30	115	Y
IH30510067/50	16.5	24.5	0.45	65.0	4.5	0.34	135	Y
IH30510069/50	19	27	0.45	65.0	4.5	0.39	150	Y